

PROMACRYL

Premium Quality Acrylic Emulsion

TECHNICAL DATA SHEET

PRODUCT DESCRIPTION

Non-toxic washable premium quality interior/exterior grade acrylic emulsion.

Available in smooth satin finish

INTENDED USES

Premium quality acrylic emulsion for applications to a wide range of substrates including common concrete, dry linings, plastered walls, brick and block walls.

Washable and scratch resistant smooth coating available in a silk or satin finish.

Suitable for use in internal /external area of residential properties, public buildings, hotels, schools, hospitals shopping malls, barracks.

PRODUCT INFORMATION

Colour White (04/001) and also available in a wide range of INSPIRED

COLOURS Tints

Gloss level Smooth satin finish

Volume Solids 40%

Theoretical Spread Rate Up to 18 m²/ litre on a smooth, non-porous substrate

Practical Spread Rate Apply appropriate loss factor

Drying Time @ 25°C (77°F)

Touch Dry: 20 Minutes Hard Dry: 2 Hours

Thinner Water

Scrub Resistance > 4000 scrubs

SURFACE PREPARATION

The performance of this product will depend upon the degree of surface preparation.

All surfaces to be coated should be dry, clean and free from mould and all other contaminations.

All old, flaky and peeled paints must be removed and sanded smooth. All holes and cracks should be filled with good filler paste and sanded smooth.

CORPORATE OFFICE & SHOWROOM | No 8A, Adetokunbo Ademola Street, Victoria Island, Lagos, Nigeria HEAD OFFICE & FACTORY | 18/24 Ajisegiri Street, Ladipo-Shogunle, Lagos, Nigeria PORT HARCOURT | 99 Rivoc Road, Trans Amadi, Port Harcourt, Nigeria



PROMACRYL

Premium Quality Acrylic Emulsion

New surfaces should be allowed to cure for at least 14 days prior to painting.

Depending on the surface a suitable primer may be required to enable proper adhesion

APPLICATION

Mixing Stir thoroughly with an agitator before use

Working Pot Life N/A
Thinner / Cleaner Water

Method of Application Brush, Roller or Spray

Work Stoppages All unused materials should be stored in tightly closed containers.

Partially filled containers may show viscosity increase or skin formation

of material after storage.

PRODUCT CHARARCTERISTICS This product is washable. Can be applied in high traffic areas. Eg:.

Schools, hospitals, hotels etc. It is a 1 to 2 coat system. Contains non

lead pigments, Durable and good opacity

HAZARD IDENTIFICATION

Main Hazard No significant hazard

HANDLING AND STORAGE

Handling Requirements Ensure there is sufficient ventilation of the area.

DO NOT handle in confined space

Storage Conditions Store in a cool, well-ventilated area.

Keep container tightly closed.

Suitable Packaging Must be kept in its original package only.

DISPOSAL CONSIDERATION

Disposal of packaging Arrange for collection by specialized disposal company.

NB: The user's attention is drawn to the possible existence of regional

or national regulations regarding disposal.



PROMACRYL

Premium Quality Acrylic Emulsion

Company Disclaimer: The information contained in the technical data sheet is believed to be accurate and true at the date of issuance but are subject to change without prior notice. We guarantee our product to conform to the specifications contained herein, however we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and liability (if any) resulting from its use is limited to replacement of the product.

Version 3 - November 2021