

PROMAGLOSS

Premium Quality Alkyd Enamel

TECHNICAL DATA SHEET

PRODUCT DESCRIPTION A premium quality alkyd enamel, with good application properties and a

high gloss finish

INTENDED USES As a cosmetic finish coat for alkyd-based systems intended for both interior and

exterior Exposure

PRODUCT INFORMATION

Colour White and available on request in a limited colour range

Gloss level High Gloss

Volume Solids 40% - 45% (Depends on Colour)

Theoretical Spreading rate 12.00 m²/litre at 35 microns dry equivalent to 83 microns wet

Practical Spreading Rate Allow appropriate loss factor

Typical Thickness 35 microns dry – equivalent to 83 microns wet

Drying Time @ 25°C (77°F)

Touch Dry:4 HoursHard Dry:24 HoursThinnerTHN1001

SURFACE PREPARATION The performance of this product will depend upon the degree of surface

preparation.

All surfaces to be coated should be dry, clean and free from mould and

other contaminations.

Accumulated dirt and soluble salts must be removed prior to painting.

Dry wire brushing will be adequate for accumulated dirt. Oil or grease should be removed by solvent cleaning.

.....

APPLICATION

Mixing This material is a one component coating. Stir thoroughly with an

agitator before use

Working Pot Life N/A

Thinner / Cleaner THN/1000

Method of Application Brush or Roller or Spray

Work Stoppages Thoroughly flush all equipment with PCMN THN/1000.

All unused materials should be stored in tightly closed containers.





PROMAGLOSS

Premium Quality Alkyd Enamel

Partially filled containers may show viscosity increase or skin formation of material after storage. Material should be filtered prior to use.

PRODUCT CHARARCTERISTICS

As with all alkyd systems, Promagloss has limited chemical and solvent resistance and is not suitable for use in immersion situations or in conditions of continuous condensation. Promagloss is not designed for application over epoxies or polyurethanes, and should not be applied over zinc-based primers because of dangers of saponification of the alkyd resin and consequent adhesion loss.

Contains non lead pigments 2 coats system

Health & Safety

Avoid contact of the material with skin and eyes.

Wear gloves and goggles

Wash off splashes immediately with soap and water.

Any eye contamination must be rapidly irrigated with copious amounts of

clean water, and immediate medical attention sought.

Please refer to Material Safety Data Sheet for additional information

HANDLING AND STORAGE

Handling Requirements Ensure there is sufficient ventilation of the area.

DO NOT handle in confined space

Storage Conditions Store in a cool, well-ventilated area.

Keep container tightly closed.

Suitable Packaging Must be kept in its original package only.

DISPOSAL CONSIDERATION

Disposal of packaging

Arrange for collection by specialized disposal company.

NB: The user's attention is drawn to the possible existence of regional

or national regulations regarding disposal.

Company Disclaimer: The information contained in the technical data sheet is believed to be accurate and true at the date of issuance but are subject to change without prior notice. We guarantee our product to conform to the specifications contained herein, however we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and liability (if any) resulting from its use is limited to replacement of the product.

Version 4 - November 2021