



PROMASCREENED

Premium Quality Wall Screed

TECHNICAL DATA SHEET

PRODUCT DESCRIPTION Promascreed is a Premium grade acrylic water-based Screed. Fungus Resistant

INTENDED USES For filling blemishes, cracks and holes on masonry surfaces and patching up surface imperfections on plastered walls.

PRODUCT INFORMATION

Colour	White
Gloss level	Matt
Volume Solids	59%
Theoretical Spread rate	Up to 1.67 m ² litre on a non-porous substrate
Practical Spread Rate	Allow appropriate loss factor
Drying Time @ 25°C (77°F)	
Touch Dry:	60 Minutes
Hard Dry:	24 Hours
Thinner	Do not dilute

SURFACE PREPARATION

Surfaces must be clean, dry and free from all defective or poorly adhering material.

All new surfaces must be completely cured before application.

Remove all loose material from cracks and open joints.

Where necessary, surfaces should be thoroughly rubbed down, using 'wet flattening' methods where possible, then wipe off with a damp, lint free cloth.

Ensure that the Wall putty dries before rainfall when used for external purpose.

Allow to dry at least 24 hours before painting with an appropriate PCMN / Plascon paint.

Stir thoroughly before use.

Dampen the area to be made good, using a clean damp sponge and then press the filler firmly into the defect, using a clean putty knife.

Leave a small excess of the filler to allow for any sinkage and rubbing down smooth when dry. Should be applied within 1mm thickness for better result.

Sand the surface with Emery Paper and wipe clean before application of subsequent coats

CORPORATE OFFICE & SHOWROOM | No 8A, Adetokunbo Ademola Street, Victoria Island, Lagos, Nigeria

HEAD OFFICE & FACTORY | 18/24 Ajisegiri Street, Ladipo-Shogunle, Lagos, Nigeria

PORT HARCOURT | 99 Rivoc Road, Trans Amadi, Port Harcourt, Nigeria

TEL +234 906 000 9502

TEL +234 1 342 9083

TEL +234 803 960 4969

www.pcmnigeria.com | info@pcmnigeria.com



PROMASCREENED

Premium Quality Wall Screed

APPLICATION

Mixing	Stir thoroughly with an agitator before use
Working Pot Life	N/A
Cleaner	Water
Method of Application	Putty Knife or Steel Trowel
Work Stoppages	All unused materials should be stored in tightly closed containers. Partially filled containers may show viscosity increase or skin formation of material after storage.

PRODUCT CHARACTERISTICS

Promascreed wall putty is high grade putty based on styrene acrylic copolymer providing excellent smoothing and filling properties. This product is not intended for use in aggressive, corrosive environments and immersion services. Contains non-lead pigments. Good adhesion to plaster and cement.

HAZARD IDENTIFICATION

Main Hazard	No significant hazard.
--------------------	------------------------

HANDLING AND STORAGE

Handling Requirements	Ensure there is sufficient ventilation of the area. DO NOT handle in confined space
Storage Conditions	Store in a cool, well-ventilated area. Keep container tightly closed.
Suitable Packaging	Must be kept in its original package only.

DISPOSAL CONSIDERATION

Disposal of packaging	Arrange for collection by specialized disposal company. NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.
------------------------------	--

Company Disclaimer: The information contained in the technical data sheet is believed to be accurate and true at the date of issuance but are subject to change without prior notice. We guarantee our product to conform to the specifications contained herein, however we make



PROMASCREEN

Premium Quality Wall Screed

no warranty of merchantability or any other warranty, express or implied, with respect to such information, and liability (if any) resulting from its use is limited to replacement of the product.

Version 3 – November 2021

CORPORATE OFFICE & SHOWROOM | No 8A, Adetokunbo Ademola Street, Victoria Island, Lagos, Nigeria
HEAD OFFICE & FACTORY | 18/24 Ajisegiri Street, Ladipo-Shogunle, Lagos, Nigeria
PORT HARCOURT | 99 Rivoc Road, Trans Amadi, Port Harcourt, Nigeria

TEL +234 906 000 9502
TEL +234 1 342 9083
TEL +234 803 960 4969

www.pcmnigeria.com | info@pcmnigeria.com