

### **PROMASHIELD**

## Premium Quality Acrylic Emulsion

#### TECHNICAL DATA SHEET

#### PRODUCT DESCRIPTION

A non-toxic, premium quality, interior /exterior grade acrylic emulsion. Excellent colour retention when subject to UV exposure and is available in a smooth matt finish.

#### **INTENDED USES**

An exterior grade quality acrylic emulsion for applications to a wide range of substrates including common concrete, plaster walls, brick and block works.

Promashield has excellent anti-mould properties and is available in a smooth matt finish ideally suited for residential properties, public buildings, hotels, schools, hospitals, shopping malls, barracks.

#### PRODUCT INFORMATION

Colour White (03/001) and also available in a wide range of INSPIRED

**COLOURS Tints** 

Gloss level Smooth Matt

Volume Solids 40%

**Theoretical Spread rate** Up to 16/m² litre on a smooth, non-porous substrate

Practical Spread Rate Allow appropriate loss factor

Drying Time @ 25°C (77°F)

 Touch Dry:
 20 Minutes

 Hard Dry:
 2 Hours

 Thinner
 Water

 pH
 7.5 – 9.0

 Scrub Resistance
 >4000 scrubs

#### **SURFACE PREPARATION**

The performance of this product will depend upon the degree of the surface preparation.

All surfaces to be coated should be dry, clean and free from contamination.

All old, flaky and peeled paints must be removed and sanded smooth. All holes and cracks should be filled with a good filler paste and sanded smooth.

New surfaces should be allowed to cure for at least 14 days prior to painting.

CORPORATE OFFICE & SHOWROOM | No 8A, Adetokunbo Ademola Street, Victoria Island, Lagos, Nigeria HEAD OFFICE & FACTORY | 18/24 Ajisegiri Street, Ladipo-Shogunle, Lagos, Nigeria PORT HARCOURT | 99 Rivoc Road, Trans Amadi, Port Harcourt, Nigeria



### **PROMASHIELD**

## Premium Quality Acrylic Emulsion

#### **APPLICATION**

Mixing Stir thoroughly with an agitator before use

Working Pot Life N/A
Thinner / Cleaner Water

Method of Application Brush, Roller or Airless Spray

Work Stoppages All unused materials should be stored in tightly closed containers.

Partially filled containers may show viscosity increase or skin formation

of material after storage.

**PRODUCT CHARARCTERISTICS** This product has a high opacity and good resistance to mild algae and

fungal attacks. Contains non-lead pigments and is durable.

It is a one to two-coat system.

HAZARD IDENTIFICATION

Main Hazard No significant hazard.

**HANDLING AND STORAGE** 

Handling Requirements Ensure there is sufficient ventilation of the area.

DO NOT handle in confined space

Storage Conditions Store in a cool, well-ventilated area.

Keep container tightly closed.

Suitable Packaging Must be kept in its original package only.

**DISPOSAL CONSIDERATION** 

**Disposal of packaging** Arrange for collection by specialized disposal company.

NB: The user's attention is drawn to the possible existence of regional

or national regulations regarding disposal.

Company Disclaimer: The information contained in the technical data sheet is believed to be accurate and true at the date of issuance but are subject to change without prior notice. We guarantee our product to conform to the specifications contained herein, however we make

CORPORATE OFFICE & SHOWROOM | No 8A, Adetokunbo Ademola Street, Victoria Island, Lagos, Nigeria HEAD OFFICE & FACTORY | 18/24 Ajisegiri Street, Ladipo-Shogunle, Lagos, Nigeria PORT HARCOURT | 99 Rivoc Road, Trans Amadi, Port Harcourt, Nigeria

TEL +234 906 000 9502 TEL +234 1 342 9083 TEL +234 803 960 4969



# **PROMASHIELD**

# Premium Quality Acrylic Emulsion

no warranty of merchantability or any other warranty, express or implied, with respect to such information, and liability (if any) resulting from its use is limited to replacement of the product.

Version 3 - November 2021