

TECHNICAL DATA SHEET

PRODUCT DESCRIPTION

A Standard quality Alkali resisting primer for new dry interior and exterior porous surfaces. It is a quick drying pigmented primer that enhances the natural qualities of its substrate.

INTENDED USES

It is ideal for use on internal and external of all types of masonry surfaces such as cement plaster, gypsum plaster, concrete, fibro cement and all composite boarding

PRODUCT INFORMATION

Colour	White
Gloss level	Matt
Volume Solids	40%
Theoretical Spreading Rate	Up to 12.5 m ² / litre on a smooth, non-porous substrate
Practical Spreading Rate	Allow appropriate loss factor
Drying Time @ 25°C (77°F)	
Touch Dry:	4 Hours
Hard Dry:	16 Hours
Thinner	THN1001

SURFACE PREPARATION

The performance of this product will be enhanced upon the degree of surface preparation. All surfaces to be coated should be dry, clean and free from oil, debris or grease. Not suitable as primer for metal surfaces

Remove all dirt, grease, loose or flaking paint. Where necessary, surfaces should be rubbed down using a suitable abrasive paper and then dusted off. Dry wire brushing will be adequate for accumulated dirt.

APPLICATION

Mixing	Stir thoroughly with an agitator before use
Working Pot Life	N/A
Thinner / Cleaner	THN1001
Method of Application	Brush or Roller



ALKAPRIMER

Standard Quality Primer

Registered office: 18/24 Ajisejiri Street,
Shogunle - Oshodi
Lagos
Nigeria



Work Stoppages

All unused materials should be stored in tightly closed containers. Partially filled containers may show viscosity increase or skin formation of material after storage.

PRODUCT CHARACTERISTICS

The product combines good alkaline resistance with good sealing properties. It serves as a sealer and primer. Do not apply during cold (below 10°C) or wet weather. New work requires 1 coat, a 2nd coat may be required on very absorbent surfaces. Product can be overcoated with most decorative finishes. Do not use or store in extreme temperatures.

HAZARD IDENTIFICATION

Main Hazard No significant hazard.

HANDLING AND STORAGE

Handling Requirements	Ensure there is sufficient ventilation of the area. DO NOT handle in confined space
Storage Conditions	Store in a cool, well-ventilated area. Keep container tightly closed.
Suitable Packaging	Must be kept in its original package only.

DISPOSAL CONSIDERATION

Disposal of packaging Arrange for collection by specialized disposal company.
NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Company Disclaimer: The information contained in the technical data sheet is believed to be accurate and true at the date of issuance but are subject to change without prior notice. We guarantee our product to conform to the specifications contained herein, however we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and liability (if any) resulting from its use is limited to replacement of the product.

Version 2 – November 2021