



Registered office: 18/24 Ajisehiri Street,
Shogunle - Oshodi
Lagos
Nigeria



CLASSIC GLOSS

Standard Quality Alkyd Enamel

TECHNICAL DATA SHEET

PRODUCT DESCRIPTION

A standard quality alkyd enamel, with good application properties and gloss finish.

INTENDED USES

It is designed for the interior and exterior protection of a variety of surfaces, such as all common metals, wood and concrete.

PRODUCT INFORMATION

| | |
|----------------------------------|--|
| Colour | White, Black and a limited Colour Range Available on request |
| Gloss level | High Gloss |
| Volume Solids | 38% - 40% |
| Theoretical Coverage | 13m ² / litre (on primed substrate) |
| Drying Time @ 25°C (77°F) | |
| Touch Dry: | 4 Hours |
| Hard Dry: | 24 Hours |
| Shelf Life | Up to 12 months |
| Thinner | THN/1000 |

SURFACE PREPARATION

The performance of this product will depend upon the degree of surface preparation.
All surfaces to be coated should be dry, clean and free from mould and other contaminations.
Accumulated dirt and soluble salts must be removed prior to painting.
Dry wire brushing will be adequate for accumulated dirt.
Surfaces should be abrasive blasted clean to Sa2^{1/2} or SSPC-SP6.
Oil or grease should be removed by solvent cleaning.

APPLICATION

| | |
|------------------------------|---|
| Mixing | Stir thoroughly with an agitator before use |
| Working Pot Life | N/A |
| Thinner / Cleaner | THN/1000 |
| Method of Application | Brush or Roller or Spray |
| Work Stoppages | Thoroughly flush all equipment with PCMN THN/1000. All unused materials should be stored in tightly closed containers. Partially filled containers may show viscosity increase or skin formation of material after storage. Material should be filtered prior to use. |



Registered office: 18/24 Ajisehiri Street,
Shogunle - Oshodi
Lagos
Nigeria



CLASSIC GLOSS

Standard Quality Alkyd Enamel

Partially filled containers may show viscosity increase or skin formation of material after storage.

PRODUCT CHARACTERISTICS

Anti-corrosive performance on hand prepared substrates is determined by the extent of the substrate preparation and the dry film thickness. This product is not intended for use in aggressive, corrosive environments and immersion services. Contains non lead pigments. 2 to 3 coats system on primed substrate.

HAZARD IDENTIFICATION

Main Hazard Flammable and harmful by inhalation

HANDLING AND STORAGE

| | |
|-----------------------|--|
| Handling Requirements | Ensure there is sufficient ventilation of the area. DO NOT handle in confined space Avoid the formation or the spread of mist in the air. Smoking is forbidden. Use non-sparking tools. |
| Storage Conditions | Store in a cool, well-ventilated area. Keep container tightly closed. Prevent the buildup of electrostatic charge in the immediate area. Do not store in extreme temperature. Ensure lighting and electrical equipment is not a source of ignition. |
| Suitable Packaging | Must be kept in its original package only. |

DISPOSAL CONSIDERATION

Disposal of packaging Arrange for collection by specialized disposal company.
NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Company Disclaimer: The information contained in the technical data sheet is believed to be accurate and true at the date of issuance but are subject to change without prior notice. We guarantee our product to conform to the specifications contained herein, however we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and liability (if any) resulting from its use is limited to replacement of the product.

Version 1 – March 2022