



Registered office: 18/24 Ajisejiri Street,
Shogunle - Oshodi
Lagos
Nigeria



HI CLASSIC ULTRA SATIN

High Quality Acrylic Emulsion

TECHNICAL DATA SHEET

PRODUCT DESCRIPTION

A non-toxic, high quality, interior/exterior grade satin acrylic emulsion.
High opacity and scrub resistance,

INTENDED USES

An exterior / Interior grade high quality acrylic emulsion for applications to a wide range of substrates including common concretes, plaster walls, brick and block work.

Hi classic Ultra satin has excellent anti-mold properties and is ideally suited for residential properties, public buildings, hotels, schools, hospitals, shopping malls, barracks.

PRODUCT INFORMATION

Colour	White (02/FS001) and limited Colour Range available on request
Gloss level	Smooth Satin
Volume Solids	60%
Theoretical Spreading rate	Up to 16m ² / litre on a smooth, non-porous surface
Practical Spreading Rate	Allow appropriate loss factors
Drying Time @ 25°C (77°F)	
Touch Dry:	20 Minutes
Hard Dry:	2 Hours
Thinner	Water
pH	7.5 – 9.0
Scrub Resistance	>3500 scrubs

SURFACE PREPARATION

The performance of this product will depend upon the degree of the surface preparation.

All surfaces to be coated should be dry, clean and free from contamination.

All old, flaky and peeled paints must be removed and sanded smooth.

All holes and cracks should be filled with a good filler paste and sanded smooth.

New surfaces should be allowed to cure for at least 14 days prior painting.



Registered office: 18/24 Ajisejiri Street,
Shogunle - Oshodi
Lagos
Nigeria



HI CLASSIC ULTRA SATIN

High Quality Acrylic Emulsion

APPLICATION

Mixing	Stir thoroughly with an agitator before use
Working Pot Life	N/A
Thinner / Cleaner	Water
Method of Application	Brush, Roller or Airless Spray
Work Stoppages	All unused materials should be stored in tightly closed containers. Partially filled containers may show viscosity increase or skin formation of material after storage.

PRODUCT CHARACTERISTICS

This product has a high opacity and good resistance to mild algae and fungal attacks.
It is a two /three -coat system on non-porous plain substrate.
Contains non lead pigments.

HAZARD IDENTIFICATION

Main Hazard No significant hazard.

HANDLING AND STORAGE

Handling Requirements	Ensure there is sufficient ventilation of the area. DO NOT handle in confined space
Storage Conditions	Store in a cool, well-ventilated area. Keep container tightly closed.
Suitable Packaging	Must be kept in its original package only.

DISPOSAL CONSIDERATION

Disposal of packaging Arrange for collection by specialized disposal company.
NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Company Disclaimer: The information contained in the technical data sheet is believed to be accurate and true at the date of issuance but are subject to change without prior notice. We guarantee our product to conform to the specifications contained herein, however we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and liability (if any) resulting from its use is limited to replacement of the product.

Version 3 – November 2021